

# Product data sheet

✉ [sales@brannan.co.uk](mailto:sales@brannan.co.uk)

☎ +44 (0)1946 816600

🌐 [brannan.co.uk](http://brannan.co.uk)

## ASTMH001 - ASTM E 100 HYDROMETERS - LOW SURFACE TENSION

The American Society for Testing and Materials (ASTM) Specification E 100 describes hydrometers using the API (American Petroleum Institute) scale and others in degrees Specific Gravity. These 330mm long plain hydrometers are adjusted at 60°F for petroleum products and other liquids of low surface tension. All hydrometers can be supplied with UKAS certification, certificate traceable to Recognised National Standard or Statement of Conformity, if required.

### Product Features:

- Adjusted at 60°F
- 330mm long
- Made in UK
- Supplied in protective, resealable plastic tube

### Product specifications:

<b>Material:</b>	Soda glass Steel shot ballast Synthetic wax resin
<b>Ranges:</b>	See table
<b>Overall length:</b>	330mm
<b>Bulb diameter:</b>	26mm
<b>Approx weight:</b>	100g (incl. 45g protective plastic tube)

ASTM Number	API Range	Division	Product number
1H	-1 to 11	0.1	09/001/0
2H	9 to 21	0.1	09/002/0
3H	19 to 31	0.1	09/003/0
4H	29 to 41	0.1	09/004/0
5H	39 to 51	0.1	09/005/0
6H	49 to 61	0.1	09/006/0
7H	59 to 71	0.1	09/007/0
8H	69 to 81	0.1	09/008/0
9H	79 to 91	0.1	09/009/0
10H	89 to 101	0.1	09/010/0

ASTM Number	Range °SG	Division	Product number
82H	0.650 to 0.700°SG	0.0005	09/082/0
83H	0.700 to 0.750°SG	0.0005	09/083/0
84H	0.750 to 0.800°SG	0.0005	09/084/0
85H	0.800 to 0.850°SG	0.0005	09/085/0
86H	0.850 to 0.900°SG	0.0005	09/086/0
87H	0.900 to 0.950°SG	0.0005	09/087/0
88H	0.950 to 1.000°SG	0.0005	09/088/0
89H	1.000 to 1.050°SG	0.0005	09/089/0
90H	1.050 to 1.100°SG	0.0005	09/090/0



View me on the website

