# **Product data sheet**





Pin I

brannan.co.uk

### ADVANCED DUAL LASER INFRARED THERMOMETER

•

•

High specification, dual laser infrared thermometers with precise infrared measurement using built in laser pointers and K-type input capabilities.

#### **Product features:**

- Precise IR and K-Type input temperature measurement
- Automatic range selection, data hold and power off function
- Standard or high range models
- °C/°F selectable
- REC datalogger function for 12 points
- MAX/MIN/DIF/AVG record
- Trigger lock
- Supplied in protective bag
- Supplied with 3 point factory certificate of calibration

#### **Product specifications:**

Product specifications.			
IR Temperature range:	See table		
K-type temperature range:	-50 to 1370°C (-58 to 2498°F)		
Optical resolution (D:S):	<b>38/705/0:</b> 13:1 / <b>38/706/0:</b> 30:1		
Response time:	<250ms		
Response wavelength:	8 to 14µ		
IR Basic accuracy:	-50 to 0°C/°F: +/- 4°C/7°F		
	0 to 500°C/°F: +/-1.5%+/-2°C/3.6°F		
K-type basic accuracy:	-50 to 1370°C/°F: +/- 1.5% +/-1°C/1.8°F		
Emissivity:	Adjustable 0.1 to 1.0		
Resolution:	0.1°C/°F		
Operating conditions:	0 to 50°C <95%RH (non-condensing)		
Storage conditions:	-20 to 70°C <80%RH		
Memory:	Storage of 12 readings		
Response time:	1 second		
Battery:	1 x 9V (included)		
CE & RoHS/WEEE:	Compliant		
Hazard information (SDS):	See brannan.co.uk for information		
LCD dimensions:	35mm x 35mm		
Product dimensions:	Gross: 250mm x 125mm x 65mm		
	Net: 192mm x 97mm x 59mm		
Product weights:	Net: 294g		
	Protective bag: 53g		

Box: 71g

Gross: 418g



View me on the website





Description	Range	Barcode	Product No
Advanced, dual laser infrared thermometer - high range	-50 to 1050°C&F	5 011405 387066	38/706/0
Replacement thermocouple wire	n/a	n/a	38/698/0

Built-in dual laser pointers

Adjustable High/Low alarm

Large backlit LCD

• Adjustable emissivity: 0.1 to 1.0

Includes 1pc thermocouple wire

## **Measurement for life.**

