Product data sheet



<u>+44 (0)1946 816600</u>

💽 <u>brannan.co.uk</u>

ANV041 - STAINLESS STEEL NEEDLE VALVE WITH VENT



Product features:

- Block and bleed valve, conical tip type.
- Provides complete shut off or adjustable throttling of the pressure media.
- M8 vent hole
- Stainless steel 316, 316L, Monel or Hastelloy C materials available
- · A choice of male, female, and socket weld connections
- NACE compliant optional
- Brannan quality

Product applications:

- · Instrument isolation and venting
- For use on gas and liquid applications
- Oil and gas
- Chemical and Petrochemical
- Power generation
- Water & wastewater
- Other process applications

Product specifications:

| Valve orientation | Straight |
|-------------------------------|--|
| Process/Instrument connection | Male x Female, Female x Female, Male x Male |
| Connection size/type | 1/4", 3/8", 1/2" BSP/BSPT/NPT |
| Max pressure | 400 bar (for max pressure up to 700 bar please contact our sales team) |
| Max temperature | 240°C |
| Body material | |
| Valve material | Choice between: |
| Bonnet material | Carbon steel, SS 304, SS 316, SS 316L, Monel, Hastelloy C |
| Stem material | |
| Tip material | |
| Stem / gland packing | PTFE or graphite |
| Stem | Type CT: Conical tip press fitted hard chrome plated |
| Stem packing area | Burnished finish for smooth valve operation |
| Safety feature | Back seating to prevent stem blowout |
| Vent | M8 |




Measurement for life.



sales@brannan.co.uk +44 (0)1946 816600 brannan.co.uk

Product dimensions:



| Size | Туре | Length A | Width B | Height (open) Max, C | Handle D | Handle OD E |
|------|------|-------------|------------|-------------------------|-------------|----------------|
| 1/4" | FxF | 70 | 25 | 63 | 40 | 10 |
| | MxF | 70 | 25 | 63 | 40 | 10 |
| | MxM | 75 | 25 | 63 | 40 | 10 |
| 3/8" | FxF | 70 | 25 | 63 | 40 | 10 |
| | MxF | 70 | 25 | 63 | 40 | 10 |
| | MxM | 75 | 25 | 63 | 40 | 10 |
| 1/2" | FxF | 75 | 32 | 83.6 | 50 | 12 |
| | MxF | 83 | 32 | 83.6 | 50 | 12 |
| | MxM | 88 | 32 | 83.6 | 50 | 12 |

All dimensions in mm

Measurement for life.



Product data sheet



brannan.co.uk <u>brannan.co.uk</u>

Product numbers:

All ANV041 needle valves are ordered to specific customer specifications. Please use below matrix to create your unique ordering product reference, using the values in bold.

| Make | Model | Wetted material | Stem packing | Process/instruments connection | Connection size & type | Extras |
|-------------------------|-------------------|-------------------------|------------------------|--|---------------------------------|--|
| Brannan (BRN) | ANV041 (ANV41) | Carbon steel (CAR) | PTFE (P) | Female to Female (FF) | 1/4" x 1/4" BSP (3) | Compliance to NACE MR-0175 (NACE) |
| | | SS304 (304) | Graphite (G) | Male to Male (MM) | 1/4" x 1/4" NPT (4) | Materials test certificate |
| | | SS316 (316) | | Male to Female (MF) | 1/4" x 1/4" BSPT (10) | (MTC) For oxygen |
| | | SS316L (316L) | | Qualitational d | 3/8" x 3/8" BSP (5) | service (O) |
| | | Monel (MON) | | Socket weld available on request | 3/8" x 3/8" NPT (6) | |
| | | Hastelloy C (HAS) | | | 3/8" x 3/8" BSPT (11) | |
| | | | | | 1/2" x 1/2" BSP (7) | |
| | | | | | 1/2" x 1/2" NPT (8) | NB. When more than one |
| | | | | | 1/2" x 1/2" BSPT (12) | extra is required, separate each code with a hyphen when building your product reference. |

Order example:

| Make | Model | Wetted material | Stem packing | Process/instruments connection | Connection size & type | Extras |
|------|-------|-----------------|--------------|--------------------------------|---------------------------|----------|
| BRN | ANV41 | 316 | Ρ | MF | 8 | NACE-MTC |

Product reference: BRNANV41/316/P/MF/8/NACE-MTC

Special product reference - 74/250/0 (BRNANV41/316/P/FF/7): SS316 needle valve with vent 1/2" BSP F x 1/2" BSP F PTFE packing



Measurement for life.