

Product data sheet

BSH001 : BS 718 : 1991 DENSITY HYDROMETERS

M50 SERIES

BS 718 : 1991 is generally aligned with ISO 387 and ISO 649. The specification includes five series and three sub-series of hydrometers, of which the most widely used are listed below. They are calibrated using the accepted units of grams per millilitre (g/ml) and are adjusted at 20°C.

The following specification refers to M50 Series. All hydrometers can be supplied with UKAS certification, certificate traceable to Recognised National Standard or Statement of Conformity, if required.

Product features:

- Calibrated using grams per millilitre (g/ml)
- Adjusted at 20°C
- 270mm long
- Made in UK
- Supplied in protective, resealable plastic tube

Product specifications:

Material:	Soda glass Steel shot ballast Synthetic wax resin
Ranges:	See table
Range span:	0.050 g/ml
Divisions:	0.001 g/ml
Accuracy:	0.001 g/ml
Overall length:	270mm
Bulb diameter:	20 - 24mm
Approx weight:	42g (incl. 14g protective plastic tube)

Range g/ml	To suit surface tension	Product number
0.60 to 0.65 g/ml	Low	10/330/0
0.65 to 0.70 g/ml		10/331/0
0.70 to 0.75 g/ml		10/332/0
0.75 to 0.80 g/ml		10/333/0
0.80 to 0.85 g/ml		10/334/0
0.85 to 0.90 g/ml		10/335/0
0.90 to 0.95 g/ml		10/336/0
0.95 to 1.00 g/ml		10/337/0
1.00 to 1.05 g/ml	Medium	10/338/0
1.05 to 1.10 g/ml		10/339/0
1.10 to 1.15 g/ml		10/340/0
1.15 to 1.20 g/ml		10/341/0
1.20 to 1.25 g/ml		10/342/0
1.25 to 1.30 g/ml		10/343/0
1.30 to 1.35 g/ml		10/344/0
1.35 to 1.40 g/ml		10/345/0
1.40 to 1.45 g/ml		10/346/0
1.45 to 1.50 g/ml		10/347/0
1.50 to 1.55 g/ml		10/348/0
1.55 to 1.60 g/ml		10/349/0
1.60 to 1.65 g/ml		10/350/0
1.65 to 1.70 g/ml		10/351/0
1.70 to 1.75 g/ml		10/352/0
1.75 to 1.80 g/ml		10/353/0
1.80 to 1.85 g/ml	10/354/0	
1.85 to 1.90 g/ml	10/355/0	
1.90 to 1.95 g/ml	10/356/0	
1.95 to 2.00 g/ml	10/357/0	

